

CLAIMS

1. A tether substantially prevented from snugly encircling an appendage or neck of a child aged five or under, thereby substantially preventing a danger of choking and/or loss of circulation while maintaining an accessory near the child, comprising;
5 at least one elongate relatively stiffer section; and
at least one relatively flexible accessory section extending from the at least one relatively stiffer section, the relatively flexible accessory section being adapted to connect to a child accessory and incapable of snugly encircling a neck or appendage in conjunction with
10 the at least one relatively stiffer section.
2. The tether according to claim 1 wherein the at least one accessory section is adapted to connect to at least one of: a C-tab, a hook, a ring, and a section of the accessory.
- 15 3. The tether according to claim 1 wherein the at least one accessory section comprises one or more of: a loop, a ring, a hook, a velcro interface, a snap, a pin and a clip.
4. The tether according to claim 3 wherein the at least one accessory section removably connects to the accessory.
20
5. The tether according to claim 1 wherein the at least one accessory section comprises a lasso.
6. The tether according to claim 5 wherein the lasso includes a stop that interfaces with the
25 lasso to control the size of lasso opening.
7. The tether according to claim 6 wherein the stop includes a bar that causes a bulge in the strands out of the plane of the lasso.
- 30 8. A kit comprising a tether according to claim 1 and including at least one accessory to which the at least one accessory section connects, the at least one accessory comprising at least one of: a baby bottle, a pacifier and a toy.

9. The kit according to claim 8 wherein the one or more included accessories are formed or imprinted with a child-pleasing likeness.
- 5 10. The kit according to claim 8 wherein the one or more included accessories are unremovably attached to the accessory connector.
11. The kit according to claim 8 wherein the at least one accessory section comprises one or more plates that connect to the one or more accessories.
- 10 12. The kit according to claim 11 wherein the one or more plates are formed or imprinted with a child-pleasing likeness.
13. The tether according to claim 1 wherein the at least one relatively stiffer section
15 comprises one or more of: plastic, metal and rubber.
14. The tether according to claim 1 wherein the at least one relatively stiffer section comprises an extension of the at least one accessory extension to which a stiff material has been attached.
- 20 15. The tether according to claim 14 wherein the stiff material comprises one or more of: plastic, metal and rubber.
16. The tether according to claim 1 wherein the at least one relatively stiffer section
25 comprises an extension of the at least one accessory extension to which a material stiffener has been added.
17. The tether according to claim 1 wherein the at least one relatively stiffer section comprises an extension of the at least one accessory extension which has been thickened to
30 form the at least one relatively stiffer section.

18. The tether according to claim 1 wherein the at least one relatively stiffer section comprises an element having at least two undulations.
19. The tether according to claim 18 wherein at least one of the at least two undulations is
5 spanned by one or more struts.
20. The tether according to claim 19 wherein the at least one relatively stiffer section comprises one or more of: plastic, metal and rubber.
21. The tether according to claim 1 additionally comprising at least one flexible anchor
10 section, adapted to connect to an anchor, extending from a second end of the elongate relatively stiffer section, the flexible anchor section being of insufficient length to encircle the neck or appendage in conjunction with the at least one relatively stiffer section.
22. The tether according to claim 21 wherein the tether includes one or more tether-
15 shortening connectors along its length.
23. The tether according to claim 21 wherein the at least one anchor section is adapted to connect to at least one of: a C-tab, hook, a ring, a bar and a structural piece of an anchor.
20
24. The tether according to claim 23 wherein the at least one anchor section comprises at least one of: a loop, a ring, a hook, a velcro interface, a snap, a pin, a clip and a lasso.
25. The tether according to claim 21 wherein the at least one anchor section comprises a
25 ground anchor.
26. The tether according to claim 1 wherein the at least one relatively stiffer section comprises two or more elongate relatively stiffer sections moveably attached to one another.
27. The tether according to claim 26 wherein one or more of the two or more elongate
30 relatively stiffer sections is curved.

28. The tether according to claim 26 wherein one of the two or more elongate relatively stiffer sections is longer than at least one other elongate relatively stiffer section.
29. The tether according to claim 26 wherein the moveable attachment comprises one or
5 more of: a hinge, a swivel and a section of material.
30. An accessory connector that connects to a baby accessory, the connector comprising:
a flexible lasso having two strands, the lasso defining an opening having an adjustable
size; and
10 a fitting, moveably connected to the two strands; wherein
moving the strands with respect to the fitting adjusts the opening size.
31. The accessory connector according to claim 30, wherein the fitting includes a cross
piece adapted to cause a bulge in the two strands out of the plane of the lasso as they pass
15 through the fitting.
32. The accessory connector according to claim 31, comprising a friction surface on at least
one of: the lasso, the strands; and the fitting.
- 20 33. The accessory connector according to claim 30, wherein the fitting includes a lock that
engages the strands to fix the lasso opening size.
34. The accessory connector according to claim 30, wherein the fitting comprises a
connector adapted to connect to at least one of: a strap, a hook and an accessory.
25
35. The accessory connector according to claim 30, wherein the lasso comprises at least one
stop that prevents disengagement of the lasso from the fitting.
36. The accessory connector according to claim 35, wherein the at least one stop comprises
30 one or more of: a ball, a tab, a child-pleasing shape, and a thickening along the element.

37. The accessory connector according to claim 30, wherein the strands comprise at least one stop that prevents disengagement of the strands from the fitting.

38. A tether substantially prevented from snugly encircling an appendage or neck of a child
5 aged five or under, thereby substantially preventing a danger of choking and/or loss of circulation while maintaining an accessory near the child, comprising;

at least one elongate relatively stiffer section having two or more undulations, at least one strut spanning at least one of the undulations; and

at least one relatively flexible accessory section extending from a first end of the at least
10 one relatively stiffer section, the relatively flexible accessory section being adapted to connect to a child accessory and incapable of snugly encircling a neck or appendage in conjunction with the at least one relatively stiffer section.

39. The tether according to claim 38 wherein the at least one relatively flexible accessory
15 section includes an accessory connector comprising:

a flexible lasso having two strands, the lasso defining an opening having an adjustable size; and

a fitting, moveably connected to the two strands; wherein

moving the strands with respect to the fitting adjusts the opening size.

20

40. The tether according to claim 39, wherein the fitting includes a lock that engages the strands to fix the lasso opening size.

41. The tether according to claim 40, wherein a friction surface is included on a portion of at
25 least one of: the strands, the fitting and the lock.

42. The tether according to claim 39, wherein the fitting comprises a cross piece, the fitting adapted to cause a bulge in the strands out of the plane of the lasso, as they pass through the fitting.

30

43. The tether according to claim 39, wherein the connection between the lasso and the flexible section comprises at least one of: a loop, a ring, a hook, a snap, a pin, a velcro interface and a clip.
- 5 44. The tether according to claim 39, wherein the lasso further comprises at least one stop that prevents disengagement of the lasso from the fitting.
45. The tether according to claim 44, wherein the at least one stop comprises one or more of: a ball, a tab, a child-pleasing shape, and a thickening along the element.
- 10 46. The tether according to claim 39, wherein the strands comprise at least one stop that prevents disengagement of the strands from the fitting.
47. The tether according to claim 38 additionally comprising at least one relatively flexible
15 anchor section, adapted to connect to an anchor, extending from a second end of the elongate relatively stiffer section, the flexible anchor section being of insufficient length to encircle the neck or appendage in conjunction with the at least one relatively stiffer section.
48. The tether according to claim 47 wherein the at least one anchor section comprises at
20 least one of: a loop, a ring, a hook, a velcro interface, a snap, a pin, a clip and a lasso.
49. The tether according to claim 47 wherein the tether further includes at least one bar and at least one tether-shortening hook spaced away from the bar, the at least one hook being adapted to removably connect to the at least one bar.

25